



Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 09/20/2018

Revision date: 09/20/2018

Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Product name : Aluma Brite
 Other means of identification : MR82

1.2. Recommended use and restrictions on use

Recommended use : Degreaser
 Restrictions on use : Not determined

1.3. Supplier

Krown Rust Control
 35 MAGNUM DRIVE
 LOG 1T0 SCHOMBERG - CANADA
 T (905) 939-8750

1.4. Emergency telephone number

Emergency number : (905) 939-8750

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Health hazard not otherwise classified, category 1 HHNOC
 Corrosive to metals, Category 1 H290
 Acute toxicity (oral), Category 2 H300
 Acute toxicity (dermal), Category 1 H310
 Acute toxicity (inhalation:dust,mist) Category 2 H330
 Skin corrosion/irritation, Category 1A H314
 Serious eye damage/eye irritation, Category 1 H318

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) :

Danger

Hazard statements (GHS-CA) :

H290 - May be corrosive to metals.
 H300+H310+H330 - Fatal if swallowed, in contact with skin or if inhaled
 H314 - Causes severe skin burns and eye damage.
 HHNOC

Precautionary statements (GHS-CA) :

P234 - Keep only in original container.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P262 - Do not get in eyes, on skin, or on clothing.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P284 - [In case of inadequate ventilation] wear respiratory protection.
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
 P302+P352 - IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a POISON CENTER or doctor.
 P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
 P321 - Specific treatment (see supplemental first aid instruction on this label)
 P330 - Rinse mouth.

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
 P363 - Wash contaminated clothing before reuse.
 P390 - Absorb spillage to prevent material damage.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P406 - Store in corrosive resistant container with a resistant inner liner.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Chemical name / Synonyms | Product identifier | % | Classification (GHS-CA) |
|------------------------------|--|----------------------|---------|---|
| Sulfuric acid | Sulphuric acid / SULFURIC ACID / Hydrogen sulfate / Sulphuric acid ...% | (CAS-No.) 7664-93-9 | 15 - 25 | HHNOC 1, HHNOC Met. Corr. 1, H290 Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 |
| Hydrofluoric acid | Hydrogen fluoride / Hydrogen fluoride, anhydrous / Hydrofluoric acid, anhydrous | (CAS-No.) 7664-39-3 | 10 - 15 | Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1A, H314 |
| 2-Butoxyethanol | 2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol / Ethylene glycol mono-n-butyl ether / 2-n-Butoxyethanol / Butyl glycol / BUTOXYETHANOL / EGBE / EGMBE / Butoxyethanol, 2- / Butyl Cellosolve / 2-Butyl Cellosolve | (CAS-No.) 111-76-2 | 5 - 10 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 |
| Alcohols, C9-11, ethoxylated | Alkyl(C9-11) alcohol, ethoxylated / Polyethylene glycol, nonyl, decyl, undecyl ether / C9-11 Pareth-3 / C9-11 PARETH-3 / C9-11 PARETH-6 / C9-11 Pareth-6 / C9-11 Pareth-8 / C9-11 Pareth-4 | (CAS-No.) 68439-46-3 | 1 | Eye Dam. 1, H318 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.
 First-aid measures after skin contact : Immediately remove contaminated clothing or footwear. Wash skin with plenty of water. Call a physician immediately. Seek medical attention if burns develop.
 First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. Consult an ophthalmologist if irritation persists.
 First-aid measures after ingestion : Call a physician immediately. Rinse mouth. Do not induce vomiting.
 First-aid measures general : Call a physician immediately. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.
 Symptoms/effects after eye contact : Serious damage to eyes.
 Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Not applicable.

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Not determined.

5.3. Specific hazards arising from the hazardous product

No additional information available

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire.
 Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : In case of large spillages: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Shovel or sweep up and put in a closed container for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray.
 Hygiene measures : Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Sulfuric acid (7664-93-9) | | |
|-------------------------------|----------------------------------|--|
| USA - ACGIH | ACGIH TWA (mg/m ³) | 0.2 mg/m ³ (thoracic particulate matter) |
| Canada (Quebec) | VECD (mg/m ³) | 3 mg/m ³ |
| Canada (Quebec) | VEMP (mg/m ³) | 1 mg/m ³ |
| Alberta | OEL STEL (mg/m ³) | 3 mg/m ³ |
| Alberta | OEL TWA (mg/m ³) | 1 mg/m ³ |
| British Columbia | OEL TWA (mg/m ³) | 0.2 mg/m ³ (Thoracic, contained in strong inorganic acid mists) |
| Ontario | OEL TWA (mg/m ³) | 0.2 mg/m ³ (thoracic) |
| Hydrofluoric acid (7664-39-3) | | |
| USA - ACGIH | ACGIH TWA (ppm) | 0.5 ppm |
| USA - ACGIH | ACGIH Ceiling (ppm) | 2 ppm |
| Canada (Quebec) | PLAFOND (mg/m ³) | 2.6 mg/m ³ |
| Canada (Quebec) | PLAFOND (ppm) | 3 ppm |
| Alberta | OEL Ceiling (mg/m ³) | 1.6 mg/m ³ |
| Alberta | OEL Ceiling (ppm) | 2 ppm |
| Alberta | OEL TWA (mg/m ³) | 0.4 mg/m ³ |
| Alberta | OEL TWA (ppm) | 0.5 ppm |
| British Columbia | OEL Ceiling (ppm) | 2 ppm |
| Ontario | OEL Ceiling (ppm) | 2 ppm |
| Ontario | OEL TWA (ppm) | 0.5 ppm |

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

| 2-Butoxyethanol (111-76-2) | | |
|----------------------------|------------------------------|----------------------|
| USA - ACGIH | ACGIH TWA (ppm) | 20 ppm |
| Canada (Quebec) | VEMP (mg/m ³) | 97 mg/m ³ |
| Canada (Quebec) | VEMP (ppm) | 20 ppm |
| Alberta | OEL TWA (mg/m ³) | 97 mg/m ³ |
| Alberta | OEL TWA (ppm) | 20 ppm |
| British Columbia | OEL TWA (ppm) | 20 ppm |
| Ontario | OEL TWA (ppm) | 20 ppm |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Materials for protective clothing:

Wear long sleeves

Hand protection:

Chemically resistant protective gloves

Eye protection:

Chemical goggles or safety glasses. Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear.
Colour : Colourless
Odour : odourless
Odour threshold : No data available
pH : < 1
Relative evaporation rate (butylacetate=1) : > 1
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : 0 °C
Boiling point : 100 °C
Flash point : Not flammable
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Not applicable
Vapour pressure : No data available
Vapour pressure at 50 °C : No data available
Relative vapour density at 20 °C : < 2
Relative density : 1.145
Solubility : Soluble.
Log Pow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : 10 mPa.s
Explosive limits : No data available

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.
- Conditions to avoid : Oxidizing agents and strong acids.
- Incompatible materials : Peroxides. Sodium hypochlorite.
- Hazardous decomposition products : Hydrogen fluoride. Hydrogen sulfide. On combustion, forms: carbon oxides (CO and CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

- Acute toxicity (oral) : Oral: Fatal if swallowed.
- Acute toxicity (dermal) : Dermal: Fatal in contact with skin.
- Acute toxicity (inhalation) : Inhalation:dust,mist: Fatal if inhaled.

| | |
|--------------------|-------------------------|
| ATE CA (oral) | 32.971 mg/kg bodyweight |
| ATE CA (dermal) | 32.248 mg/kg bodyweight |
| ATE CA (dust,mist) | 0.124 mg/l/4h |

Alcohols, C9-11, ethoxylated (68439-46-3)

| | |
|----------------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rat | > 5000 mg/kg |
| LC50 inhalation rat (mg/l) | > 20 mg/l/4h |

Sulfuric acid (7664-93-9)

| | |
|----------------------------|---|
| LD50 oral rat | 2140 mg/kg |
| LD50 dermal rat | > 5000 mg/kg |
| LC50 inhalation rat (mg/l) | 103 (85 - 103) mg/m ³ (Exposure time: 1 h) |

Hydrofluoric acid (7664-39-3)

| | |
|----------------------------|--------------------------------|
| LC50 inhalation rat (mg/l) | 0.79 mg/l (Exposure time: 1 h) |
|----------------------------|--------------------------------|

2-Butoxyethanol (111-76-2)

| | |
|---------------------------|------------|
| LD50 oral rat | 470 mg/kg |
| LD50 dermal rabbit | 99 mg/kg |
| LC50 inhalation rat (ppm) | 486 ppm/4h |

- Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: < 1
- Serious eye damage/irritation : Causes serious eye damage.
pH: < 1
- Respiratory or skin sensitization : Not classified
- Germ cell mutagenicity : Not classified
- Carcinogenicity : Not classified
- Reproductive toxicity : Not classified
- STOT-single exposure : Not classified
- STOT-repeated exposure : Not classified
- Aspiration hazard : Not classified
- Symptoms/effects after skin contact : Burns.
- Symptoms/effects after eye contact : Serious damage to eyes.
- Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

- Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Acute aquatic toxicity : Not classified
 Chronic aquatic toxicity : Not classified

| Sulfuric acid (7664-93-9) | |
|---------------------------|--|
| LC50 fish 1 | > 500 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static]) |
| BCF fish 1 | (no bioaccumulation) |

| Hydrofluoric acid (7664-39-3) | |
|-------------------------------|---|
| EC50 Daphnia 1 | 270 mg/l (Exposure time: 48 h - Species: Daphnia species) |
| BCF fish 1 | (no bioaccumulation) |
| Log Pow | -1.4 |

| 2-Butoxyethanol (111-76-2) | |
|----------------------------|---|
| LC50 fish 1 | 1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC50 fish 2 | 2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus) |
| EC50 Daphnia 1 | > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Log Pow | 0.81 (at 25 °C) |

12.2. Persistence and degradability

| Aluma Brite | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| Aluma Brite | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| Sulfuric acid (7664-93-9) | |
|---------------------------|----------------------|
| BCF fish 1 | (no bioaccumulation) |

| Hydrofluoric acid (7664-39-3) | |
|-------------------------------|----------------------|
| BCF fish 1 | (no bioaccumulation) |
| Log Pow | -1.4 |

| 2-Butoxyethanol (111-76-2) | |
|----------------------------|-----------------|
| Log Pow | 0.81 (at 25 °C) |

12.4. Mobility in soil

| Aluma Brite | |
|----------------|------------------|
| Ecology - soil | Not established. |

| Hydrofluoric acid (7664-39-3) | |
|-------------------------------|------|
| Log Pow | -1.4 |

| 2-Butoxyethanol (111-76-2) | |
|----------------------------|-----------------|
| Log Pow | 0.81 (at 25 °C) |

12.5. Other adverse effects

Ozone : Not classified
 Effect on the global warming : Not established.

| Hydrofluoric acid (7664-39-3) | |
|--|-----|
| 1990 Hazardous Air Pollutant (Clean Air Act) | Yes |

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
 Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1786
 Packing group : I - Great Danger
 TDG Primary Hazard Classes : 8 - Class 8 - Corrosives
 TDG Subsidiary Classes : 6.1

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Transport document description : UN1786 HYDROFLUORIC ACID AND SULFURIC ACID MIXTURE, 8 (6.1), I
Proper Shipping Name (Transportation of Dangerous Goods) : HYDROFLUORIC ACID AND SULFURIC ACID MIXTURE

Hazard labels (TDG) : 8 - Corrosive substances
6.1 - Toxic substances



ERAP Index : 1 000
Explosive Limit and Limited Quantity Index : 0
Passenger Carrying Ship Index : Forbidden
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : Forbidden

14.2. Transport information/DOT

Department of Transport

DOT NA no. : UN1786
UN-No.(DOT) : 1786
Packing group (DOT) : I - Great Danger
Transport document description : UN1786 Hydrofluoric acid and Sulfuric acid mixtures, 8 (6.1), I
Proper Shipping Name (DOT) : Hydrofluoric acid and Sulfuric acid mixtures
Contains Statement Field Selection (DOT) :
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Division (DOT) : 8
Hazard labels (DOT) : 8 - Corrosive
6.1 - Poison



Dangerous for the environment : No
DOT Special Provisions (49 CFR 172.102) : A6 - For combination packagings, if plastic inner packagings are used, they must be packed in tightly closed metal receptacles before packing in outer packagings.
A7 - Steel packagings must be corrosion-resistant or have protection against corrosion.
B15 - Packagings must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance.
B23 - Tanks must be made of steel that is rubber lined or unlined. Unlined tanks must be passivated before being placed in service. If unlined tanks are washed out with water, they must be re-passivated prior to return to service. Lading in unlined tanks must be inhibited so that the corrosive effect on steel is not greater than that of hydrofluoric acid of 65 percent concentration.
N5 - Glass materials of construction are not authorized for any part of a packaging which is normally in contact with the hazardous material.
N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.
T10 - 4 6 mm Prohibited 178.275(g)(3).
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
TP12 - This material is considered highly corrosive to steel.
TP13 - Self-contained breathing apparatus must be provided when this hazardous material is transported by sea.
DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Packaging Non Bulk (49 CFR 173.xxx) : 201
DOT Packaging Bulk (49 CFR 173.xxx) : 243

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

| | |
|--|---|
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : Forbidden |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 2.5 L |
| DOT Vessel Stowage Location | : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded. |
| DOT Vessel Stowage Other | : 40 - Stow "clear of living quarters" |
| Emergency Response Guide (ERG) Number | : 157 |
| Other information | : No supplementary information available. |

14.3. Air and sea transport

IMDG

| | |
|---------------------------------------|--|
| UN-No. (IMDG) | : 1786 |
| Proper Shipping Name (IMDG) | : HYDROFLUORIC ACID AND SULPHURIC ACID MIXTURE |
| Transport document description (IMDG) | : UN 1786 HYDROFLUORIC ACID AND SULPHURIC ACID MIXTURE, 8 (6.1), I |
| Class (IMDG) | : 8 - Corrosive substances |
| Packing group (IMDG) | : I - substances presenting high danger |

IATA

| | |
|---------------------------------------|--|
| UN-No. (IATA) | : 1786 |
| Proper Shipping Name (IATA) | : Hydrofluoric acid and sulphuric acid mixture |
| Transport document description (IATA) | : UN 1786 Hydrofluoric acid and sulphuric acid mixture, 8 (6.1), I |
| Class (IATA) | : 8 - Corrosives |
| Packing group (IATA) | : I - Great Danger |

SECTION 15: Regulatory information

15.1. National regulations

| |
|---|
| Aluma Brite |
| Listed on the Canadian DSL (Domestic Substances List) |
| Alcohols, C9-11, ethoxylated (68439-46-3) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Sulfuric acid (7664-93-9) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Hydrofluoric acid (7664-39-3) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2-Butoxyethanol (111-76-2) |
| Listed on the Canadian DSL (Domestic Substances List) |

15.2. International regulations

| |
|--|
| Alcohols, C9-11, ethoxylated (68439-46-3) |
| Listed on the AICS (Australian Inventory of Chemical Substances) |
| Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) |
| Listed on the Korean ECL (Existing Chemicals List) |
| Listed on NZIoC (New Zealand Inventory of Chemicals) |
| Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Listed on INSQ (Mexican National Inventory of Chemical Substances) |
| Sulfuric acid (7664-93-9) |
| Listed on the AICS (Australian Inventory of Chemical Substances) |
| Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) |
| Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory |
| Listed on the Japanese ISHL (Industrial Safety and Health Law) |
| Listed on the Korean ECL (Existing Chemicals List) |
| Listed on NZIoC (New Zealand Inventory of Chemicals) |
| Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Japanese Poisonous and Deleterious Substances Control Law |
| Listed on INSQ (Mexican National Inventory of Chemical Substances) |
| Listed on Turkish inventory of chemical |

Aluma Brite

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

| Hydrofluoric acid (7664-39-3) | |
|---|-----|
| Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the United States TSCA (Toxic Substances Control Act) inventory Japanese Poisonous and Deleterious Substances Control Law Japanese Pollutant Release and Transfer Register Law (PRTR Law) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on Turkish inventory of chemical | |
| 2-Butoxyethanol (111-76-2) | |
| Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on Turkish inventory of chemical | |
| Toxic Substance (CEPA – Schedule I) | Yes |

SECTION 16: Other information

Date of issue : 09/20/2018

Revision date : 09/20/2018

Other information : **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H-statements:

| | |
|------|--|
| H227 | Combustible liquid |
| H290 | May be corrosive to metals. |
| H300 | Fatal if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |

SDS Canada (GHS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product