Canadian Krown Dealers Inc. 35 Magnum Dr. Schomberg, Ontario, L0G 1T0 Canada (905)939-8750 / 1(800)267-5744

CODE: KR-063400

PRODUCT: Krown KL FSM Extreme Duty Chain Lube - 400 g

SECTION 01: IDENTIFICATION

Product Item Numbers..... KR-063400

Product Identity..... Krown KL FSM Extreme Duty Chain Lube - 400 g

Manufacturer..... Empack Spraytech Inc.

98 Walker Drive Brampton Ontario

Canada L6T 4H6 905-792-6571

24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800)

424-9300.

Recommended Use..... Lubricant, Penetrant, Rust Inhibitor.

Chemical Family..... Mixture.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:

Signal Word..... WARNING.

Hazard Classification:

Physical Hazards..... Aerosol. Gases Under Pressure - Liquefied Gas .

Health Hazards..... Not Classified. Environmental Hazards..... Not Classified.

H229:Pressurised container: May burst if heated (3). H280:Contains gas under pressure; Hazard Statement.....

may explode if heated (L).

Precautionary Statements: P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Prevention....

No smoking. P251:Do not pierce or burn, even after use.

None. Response.....

P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Storage.....

P403:Store in a well ventilated place.

P501:Dispose of contents/container in accordance with local, regional, national, and/or Disposal.....

international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

Classified according to:.... Canada's Hazardous Products Act/Hazardous Products Regulations (WHMIS 2015) and

Occupational Safety and Health Administration (OSHA).

SECTION 03: COMPOSITION/INFOR	RMATION ON INGREDIENTS	5
HAZARDOUS INGREDIENTS	CAS#	WT. %

10-30 1,1,1,2 Tetrafluoroethane 811-97-2

SECTION 04: FIRST-AID MEASURES

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain Inhalation..... immediate medical assistance. Skin Contact.....

Immediately flush the contaminated skin with soap and water. If this chemical penetrates clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention . Check for and remove contact lenses. Immediately flush eyes with water for a minimum of

Eye Contact.....

15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.

If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. Ingestion.....

Most important symptoms/effects, acute .. and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.



PRODUCT: Krown KL FSM Extreme Duty Chain Lube - 400 g

SECTION 05: FIRE-FIGHTING MEASURES

Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Suitable Extinguishing Media..... Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire. Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified Organic Compounds.

Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.

General Fire Hazards..... Non Flammable Aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid

walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate

CODE: KR-063400

personal protective equipment (see Section 08).

Methods and Materials for Containment ..

and Cleaning Up

Environmental Precautions.....

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Wash with plenty of water.

Avoid breathing vapours or mists. Never pierce, drill, grind, cut, saw or weld any empty Precautions for Safe Handling.....

container. Do not eat or drink while working. See Section 08 for Protective Personal

Conditions for Safe Storage including any

Incompatibilities

Keep container tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Do not store in direct sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

	ACGIH TLV		OSHA PEL			NIOSH
INGREDIENTS	TWA	STEL	PEL	STEL	REL	

1,1,1,2 Tetrafluoroethane Not available Not available Not available Not available Not available Appropriate Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit

Value if unprotected personnel are involved. Ensure that eyewash stations and safety

showers are available.

Individual Protection Measures:

Eye/Face Protection.....

Skin Protection.....

Respiratory Protection.....

Thermal Hazards..... General Hygiene Considerations.....

Chemical splash goggles are recommended.

Use appropriate protective clothing to avoid skin contact if required.

Avoid breathing dust/fume/gas/mist/vapors/spray. If permissible levels are exceeded use

NIOSH mechanical filter/organic vapor cartridge or an air-supplier.

None Known.

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Aerosol. Light Brown. Physical Appearance..... Odor..... N/A. Odor Threshold (ppm) Specific Gravity (Liquid)..... Vapour Density (Air=1)..... N/A. 0.835-0.875. 3.25. (Propellant). Aerosol Vapour Pressure (psig, 21°C)..... 75-95. pH......Boiling Point (Propellant), ° C......Melting/Freezing Point (°C)..... N/A. - 26.0. -101. (Propellant). Flash Point (°C), Method..... N/A. N/A.

Flashback..... Evaporation Rate (n-Butyl Acetate = 1)..... N/A. VOC Content.....

Solubility in water..... 0.9 g/ Molecular weight 102.03. 743 °C @ 101.325 kPa. (Propellant).

Auto Ignition Temperature (°C)..... Lower Flammable Limit (% Vol)..... Upper Flammable Limit (% Vol)..... N/A.

CODE: KR-063400

PRODUCT: Krown KL FSM Extreme Duty Chain Lube - 400 g

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

n-Octanol/Water Partition Coefficient...... log Pow: 1.06. (Propellant).

Viscosity.....

SECTION 10: STABILITY AND REACTIVITY

Reactivity No hazardous reactions.

Chemical Stability..... Stable under the recommended storage and handling conditions.

Possibility of Hazardous Reactions..... It may catch fire on contact with oxidizing mineral acids.

Conditions to Avoid..... Heat, flames, sparks.

Incompatible Materials..... None known.

Hazardous Decomposition Products...... In combustion emits toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

1,1,1,2 Tetrafluoroethane >500,000 ppm (Rat - 4hrs) Not available

Information on Likely Routes of Exposure: Routes of entry - Inhalation..... Yes. Routes of entry - Skin & Eye.....

No. Routes of entry - Ingestion..... Routes of entry - Skin Absorption..... No. Symptoms Related to the Physical,

Chemical and Toxicological Characteristics Acute Toxicity..... N/A. Skin Corrosion/Irritation..... N/A. N/A.

Serious Eye Damage/Eye Irritation..... Respiratory or Skin Sensitization..... N/A.

Germ Cell Mutagenicity..... No data available to indicate product or any components present at greater than 0.1% are mutagenic.

Carcinogenicity.....Reproductive Toxicity.....

Persistence and degradability

(CEPA)

Based on available data, the classification criteria are not met.

STOT - Single Exposure..... No data available. STOT - Repeated Exposure..... No data available. Aspiration Hazard..... No data available.

Chronic Effects..... No known adverse effects.

SECTION 12: ECOLOGICAL INFORMATION

May be dangerous for the environment. No data is available on the product itself. Should Ecotoxicity.....

not be released into the environment. The product itself has not been tested. The product itself has not been tested.

Bioaccumulation Potential..... Mobility in Soil.....Other Adverse Effects..... The product itself has not been tested.

None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and

must be disposed of in accordance with current local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.2.

UN1950, AEROSOLS, Class 2.2, LTD QTY, Consumer Commodity, ORM-D. UN1950, AEROSOLS, Class 2.2.

IATA (International- Air)..... UN1950, AEROSOLS, Class 2.2, LTD QTY.

SECTION 15: REGULATORY INFORMATION

WHMIS Classification. A: Compressed gas. Canada Regulations:....

Canadian Environmental Protection Act ... All ingredients listed appear on the Domestic Substances List (DSL).

ÙS Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication



Standard.

CODE: KR-063400

PRODUCT: Krown KL FSM Extreme Duty Chain Lube - 400 g

SECTION 16: OTHER INFORMATION

Disclaimer	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
Prepared by	Materials Information System STOT: Specific Target Organ Toxicity. Regulatory Affairs OCT 04/2018